

RattlerV² 25-320

THERMAL IMAGING RIFLE SCOPE

The NEW RattlerV² is one of the most highly-anticipated product releases. Improving on what is already considered the best-selling thermal rifle scope product family in the United States, the RattlerV² brings many of the most sought after design improvements into one sleek new housing. These improvements include, but are not limited to: dramatically expanded battery life offered through the unit's proprietary removable and rechargeable battery system, which will afford users 6.5 hours on a single charge (2 included), an expanded built-in reticle assortment, expanded brightness and contrast settings, shot activated recording with sound and new 12-micron thermal sensor that have the highest rated sensitivity rating (sub-20 mK) on the market. For a product family which was already boasted one of the best value propositions in the market, the new RattlerV²'s will only expand on that reputation.

The RattlerV² 25-320 with a 25mm Germanium lens is the perfect addition to any hunter's arsenal. Equipped with a 320x256 resolution thermal sensor, these unit has 3.5X magnification, and a detection range of 1200 meters. This base magnification allows for a wide field of view, which many hog hunters prefer, as it allows them to see and track multiple animals in a group at once.

- Superior sub-20 milikelvin thermal sensitivity
- 320x256 resolution with 12-micron sensor
- Fast 50Hz imaging
- High resolution OLED display
- Adjustable color palettes
- Various reticle types and colors
- 1x, 2x, 4x, 8x digital zoom
- On-board video/audio recording and image capture
- Built-in EMMC storage (16 GB)
- Shot Activated Recording (SAR)
- Wi-Fi data transmission
- Stadiametric rangefinder
- Standby mode
- Over 6.5 hours battery life
- External power supply compatibility
- Waterproof & shockproof
- 5-year warranty

Equipment described herein is subject to US export regulations and may require a license prior to export. Diversion contrary to US law is prohibited.



SPECIFICATIONS

Detector	12µm VOx Uncooled Focal Plane Array
Resolution	320 x 256
NETD	Less than 20 mK (25°C, F# = 1.0)
Refresh Rate	50 Hz
Lens System	25 mm; F/1.0
Magnification	3.5x - 28x
Field of View	7.0° x 5.3°
Diopter Adjustment	-5 to +5 diopters
Focus Range	7 m to infinity
Exit Pupil	6 mm
Eye Relief	45 mm
Digital Zoom	1x, 2x, 4x, 8x
Detection Range (6' object)	1200 m/yd
Display	0.39-inch, OLED, 1024x768
Palettes	Black Hot, White Hot, Red Hot, Fusion
Flat Field Correction	Auto, Manual, Semi-Auto
Scene Mode	Cold, Warm
Boresight Adjustment	Digital Controlled
Video/Audio Recording	Yes
Image Capture	Yes
Standby Mode	Yes
Storage	Built-in EMMC (16 GB)
PIP	Yes
Defective Pixel Correction	Yes
WiFi Hotspot	Yes
Hot Track	Yes
Reticle	10 types, 4 colors, on/off
Distance Measurement	Yes (Stadiametric)
Shot Activated Recording (SAR)	Yes
Battery Type	Replaceable and Rechargeable Li-ion Battery
Battery Life (Operating, 20°C)	Over 6.5 hours (25°C, with WiFi off)
External Power Supply	5 VDC, 2 A, USB Type-C
Operating Temperature Range	-30°C to +55°C (-22°F to 131°F)
Protection Level	IP67
Max. Recoil	1000 g/0.4 ms
Weight (w/o mount and battery)	0.49 kg (1.08 lb)
Dimensions (w/o mount)	219 x 68 x 67 mm (8.5 x 2.7 x 2.6 in)
Package Includes	Thermal Imaging Rifle Scope, Mount, Two Rechargeable Battery, Charger, USB Cable, Lens Cloth, Manual, Carrying Case

Specifications are subject to change without notice.
Images are for illustration purposes only.



MAIN OFFICE | 173 West Main Street | PO Box 962 | Springerville, AZ 85938, USA
Tel. +1.928.333.4300 | info@agmglobalvision.com | www.agmglobalvision.com

EUROPEAN OFFICE | #6 Andrey Lyapchev Blvd | Sofia, P.C. 1756 | Bulgaria
Tel. +35.988.560.0326 | info@agmglobalvision.eu | www.agmglobalvision.eu

www.agmglobalvision.com